



# OmniRidge® Pro

with Enhanced Weather Protection

External Venturi and "Omni" baffles provide enhanced airflow.



Sonic welded fiberglass screen provides enhanced weather protection.

Unique "posi-tabs" contour to shingles for improved weather protection.

Continuous molded end plug and underlap prohibit weather infiltration.

Fully supported nail holes.

## PRO4SWN FEATURES:

- Sonic welded fiberglass screen provides enhanced weather protection.
- Advanced low profile design.
- Includes 2½" ring shank nails, 30 nails per piece.
- Internal baffles.
- External "Omni" baffles.
- External Venturi baffle.
- "Posi-tabs" contour to shingles for improved weather protection.
- Weatherproof underlapping joints.
- 6 drain holes per side per foot.
- 18 square inches of Net Free Area per linear foot.
- 10 supported nail holes
- Preformed to 2/12 pitch.
- Fits roof pitches 2/12 to 16/12.
- Molded-in shingle nail lines, reinforced every 2 inches.
- Slot width guide lines.
- Continuous molded end plug for improved weather protection.
- **Lifetime Limited Warranty.**



Model	Length (ft.)	NFA (in. <sup>2</sup> )	Roof Pitch	Packaged
PRO4SWN	4'	72	2/12 To 16/12	10 Per Box

How many PRO4SWN vents do you need?

ATTIC FLOOR SPACE IN SQ FT:	1000										1500										2000										2500										3000										3500									
	Intake					Exhaust					Intake					Exhaust					Intake					Exhaust					Intake					Exhaust																								
PRO4SWN	14'	11	7	4	4	4	3	3	4	7	20'	15	10	6	5	5	5	6	10	27'	20	14	8	7	6	6	8	14	34'	25	17	10	9	7	10	17	40'	29	20	12	10	9	12	20	47'	34	23	14	12	10	14	24								